

IN THE CLAIMS:

24. (New) A multi-part lanyard connector that couples to a lanyard substrate and selectively couples to an attachment to thereby form a lanyard system, the multi-part lanyard connector enabling convenient disengagement at multiple connection points, the lanyard connector comprising:

(A) a lanyard connector body comprising:

a first body portion that is configured to couple to a lanyard substrate, the first portion having a proximal portion and a distal portion, wherein the proximal portion of the first portion is configured to couple to a lanyard substrate;

a second body portion that is configured to be selectively disengaged from the first body portion, the second body portion having a proximal portion and a distal portion, the proximal portion of the second body portion selectively coupling to the distal portion of the first body portion; and

(B ) a neck extending distally from the distal portion of the first body portion, a distal portion of the neck being configured to be disposed within and couple to a portion of an attachment to thereby form a lanyard system, such that a user can selectively detach the first body portion from the second body portion and can selectively detach an attachment from the distally extending neck.

25. (New) A lanyard connector as recited in claim 24, wherein the first body portion selectively buckles onto the second body portion.

26. (New) A lanyard connector as recited in claim 24, wherein the distal portion of the first body portion comprises a female portion and the proximal portion of the second body portion comprises a male portion, the male portion selectively buckling into the female portion.

27. (New) A lanyard connector as recited in claim 24, wherein the distally extending neck enables the attachment to rotate about the neck.

28. (New) A lanyard connector as recited in claim 24, wherein the distally extending neck comprises a split neck.

29. (New) A lanyard connector as recited in claim 24, wherein the distally extending neck comprises a split neck having first and second opposing tapering portions configured such that the tapering portions contact a portion of an attachment when the attachment is mounted thereon.

30. (New) A lanyard connector as recited in claim 24, wherein the distally extending neck engages the attachment in a snap-fitting relationship.

31. (New) A lanyard connector as recited in claim 24, wherein the neck comprises a split neck comprising opposing right and left neck members, each neck member comprising a thinner proximal member and a distal, wider skirt member, wherein the proximal members collectively form a proximal portion having a substantially circular cross section and the skirt

members collectively form a skirt portion which tapers proximally, widening as they proceed toward the lanyard connector body.

32. (New) A multi-part lanyard connector that couples to a lanyard substrate and selectively couples to an attachment to thereby form a lanyard system, the multi-part lanyard connector enabling convenient disengagement at multiple connection points, the lanyard connector comprising:

(A) a lanyard connector body comprising:

a first body portion that is configured to couple to a lanyard substrate, the first portion having a proximal portion and a distal portion, wherein the proximal portion of the first portion is configured to couple to a lanyard substrate;

a second body portion that is configured to be selectively disengaged from the first body portion, the second body portion having a proximal portion and a distal portion, the proximal portion of the second body portion selectively coupling to the distal portion of the first body portion; and

(B) a split neck extending distally from the distal portion of the first body portion, a distal portion of the neck being configured to be selectively disposed within and couple to a portion of an attachment in a snap-fitting, rotating engagement, to thereby form a lanyard system, the split neck having first and second opposing tapering portions configured such that the tapering portions contact a portion of an attachment when the attachment is mounted thereon, and such that a user can selectively detach the first body portion from the second body portion and can selectively detach an attachment from the distally extending neck.

09/54/297

33. (New) A multi-part lanyard connector that couples to a lanyard substrate and selectively couples to an attachment to thereby form a lanyard system, the multi-part lanyard connector enabling convenient disengagement at multiple connection points, the lanyard connector comprising:

a female buckle portion that is configured to couple to a lanyard substrate, the female buckle portion having a proximal portion and a distal portion, wherein the proximal portion of the first portion is configured to couple to a lanyard substrate;

a dual male buckle portion that is configured to be selectively disengaged from the female buckle portion, the dual male buckle portion having: (i) a proximal portion and a distal portion, the proximal portion of the dual male buckle portion comprising a plurality of protuberances that selectively couple to the distal portion of the female buckle portion; and (ii) a distally extending split neck extending from an opposing side of the dual male buckle portion, the neck being configured to be disposed within and couple to a portion of an attachment in a snap-fitting, rotating engaging with the attachment,

wherein the neck comprises a split neck comprising opposing right and left neck members, each neck member comprising a thinner proximal member and a distal, wider skirt member, the skirt members tapering and widening proximally,

such that an attachment can be selectively, snap fit onto the split neck in rotating engagement with the split neck and such that a user can selectively detach the male buckle portion from the female buckle portion and can selectively detach an attachment from the distally extending neck.